

Atkins Limited		Page 1
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Existing Network Details for Foul - Main

PN	Length (m)	Fall (1:X)	Slope	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section	Type
F1.000	29.947	0.499	60.0	0.000	5.00		0.1	1.500	o 225	Pipe/Conduit	
F1.001	17.355	0.289	60.1	0.000	0.00		0.1	1.500	o 225	Pipe/Conduit	
F1.002	12.882	0.215	59.9	0.000	0.00		0.0	1.500	o 225	Pipe/Conduit	
F2.000	34.519	0.777	44.4	0.000	5.00		0.2	1.500	o 225	Pipe/Conduit	
F1.003	61.036	0.763	80.0	0.000	0.00		0.4	1.500	o 225	Pipe/Conduit	
F3.000	53.673	1.579	34.0	0.000	5.00		0.3	1.500	o 225	Pipe/Conduit	

Network Results Table

PN	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Vel (m/s)	Cap (l/s)
F1.000	120.985	0.000	0.1	1.48	59.0
F1.001	120.486	0.000	0.2	1.48	59.0
F1.002	118.775	0.000	0.2	1.48	59.0
F2.000	119.325	0.000	0.2	1.72	68.6
F1.003	118.560	0.000	0.7	1.28	51.1
F3.000	119.376	0.000	0.3	1.97	78.4

Atkins Limited		Page 2
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Existing Network Details for Foul - Main

PN	Length (m)	Fall (1:X)	Slope (ha)	I.Area (mins)	T.E. (s)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type
F4.000	36.460	1.053	34.6	0.000	5.00		0.3	1.500	o 225	Pipe/Conduit
F1.004	38.376	0.203	189.0	0.000	0.00		0.2	1.500	o 225	Pipe/Conduit
F1.005	14.168	0.075	189.0	0.000	0.00		0.1	1.500	o 225	Pipe/Conduit
F1.006	19.050	0.314	60.7	0.000	0.00		0.2	1.500	o 225	Pipe/Conduit
F5.000	46.044	2.348	19.6	0.000	5.00		0.2	1.500	o 225	Pipe/Conduit
F1.007	25.575	1.174	21.8	0.000	0.00		0.1	1.500	o 225	Pipe/Conduit
F1.008	38.723	2.460	15.7	0.000	0.00		0.3	1.500	o 225	Pipe/Conduit

Network Results Table

PN	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Vel (m/s)	Cap (l/s)
F4.000	118.850	0.000	0.3	1.95	77.7
F1.004	117.797	0.000	1.5	0.83	33.1
F1.005	117.594	0.000	1.5	0.83	33.1
F1.006	117.519	0.000	1.7	1.48	58.7
F5.000	120.011	0.000	0.2	2.60	103.3
F1.007	117.205	0.000	2.1	2.47	98.0
F1.008	116.031	0.000	2.4	2.90	115.4

Atkins Limited		Page 3
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Existing Network Details for Foul - Main

PN	Length (m)	Fall (1:X)	Slope (ha)	I.Area (mins)	T.E. (ha)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type
F1.009	21.189	0.918	23.1	0.000	0.000	0.00	0.3	1.500	o 225	Pipe/Conduit
F6.000	50.261	1.140	44.1	0.000	5.000	5.00	0.4	1.500	o 225	Pipe/Conduit
F6.001	22.860	0.523	43.7	0.000	0.000	0.00	0.1	1.500	o 225	Pipe/Conduit
F7.000	29.693	1.188	25.0	0.000	5.000	5.00	0.2	1.500	o 225	Pipe/Conduit
F7.001	21.057	0.880	23.9	0.000	0.000	0.00	0.1	1.500	o 225	Pipe/Conduit
F6.002	10.927	0.380	28.8	0.000	0.000	0.00	0.1	1.500	o 225	Pipe/Conduit
F6.003	16.379	0.199	82.3	0.000	0.000	0.00	0.0	1.500	o 225	Pipe/Conduit

Network Results Table

PN	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Vel (m/s)	Cap (l/s)
F1.009	113.571	0.000	2.6	2.39	95.2
F6.000	117.373	0.000	0.4	1.73	68.9
F6.001	115.920	0.000	0.5	1.74	69.1
F7.000	117.778	0.000	0.2	2.30	91.5
F7.001	116.590	0.000	0.3	2.35	93.5
F6.002	115.397	0.000	0.9	2.15	85.3
F6.003	115.017	0.000	0.9	1.27	50.3

Atkins Limited		Page 4
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Existing Network Details for Foul - Main

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k SECT (mm)	HYD DIA (mm)	Section Type
F8.000	74.944	1.500	50.0	0.000	5.00		0.4	1.500	o 225 Pipe/Conduit
F6.004	17.208	0.319	53.9	0.000	0.00		0.0	1.500	o 225 Pipe/Conduit
F6.005	27.110	0.559	48.5	0.000	0.00		0.1	1.500	o 225 Pipe/Conduit
F6.006	23.807	0.749	31.8	0.000	0.00		0.1	1.500	o 225 Pipe/Conduit
F6.007	15.194	0.576	26.4	0.000	0.00		0.0	1.500	o 225 Pipe/Conduit
F1.010	32.780	0.998	32.8	0.000	0.00		0.0	1.500	o 225 Pipe/Conduit
F1.011	53.685	2.868	18.7	0.000	0.00		0.0	1.500	o 225 Pipe/Conduit

Network Results Table

PN	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Vel (m/s)	Cap (l/s)
F8.000	116.631	0.000		0.4	1.63 64.7
F6.004	114.818	0.000		1.3	1.56 62.2
F6.005	114.499	0.000		1.4	1.65 65.6
F6.006	113.940	0.000		1.5	2.04 81.1
F6.007	113.191	0.000		1.5	2.24 89.1
F1.010	112.398	0.000		4.1	2.01 79.8
F1.011	111.400	0.000		4.1	2.66 105.8

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	Page 5
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Existing Network Details for Foul - Main

PN	Length (m)	Fall (1:X)	Slope (ha)	I.Area (mins)	T.E. (ha)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section	Type
F1.012	38.476	1.977	19.5	0.000	0.00	0.0	1.500	o	225	Pipe/Conduit	
F1.013	14.946	0.217	68.9	0.000	0.00	0.0	1.500	o	225	Pipe/Conduit	

Network Results Table

PN	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Vel (m/s)	Cap (l/s)
F1.012	108.532	0.000	4.1	2.61	103.7
F1.013	106.555	0.000	4.1	1.38	55.0

Atkins Limited		Page 6
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Manhole Schedules for Foul - Main

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam., L*W (mm)	Pipe Out			PN	Pipes In			Backdrop (mm)
					PN	Invert Level (m)	Diameter (mm)		PN	Invert Level (m)	Diameter (mm)	
F5	123.190	2.205	Open Manhole	1200	F1.000	120.985	225					
F6	122.332	1.846	Open Manhole	1200	F1.001	120.486	225	F1.000	120.486	225		
F8	121.828	3.053	Open Manhole	1200	F1.002	118.775	225	F1.001	120.197	225		1422
F12	120.950	1.625	Open Manhole	1200	F2.000	119.325	225					
F13	121.436	2.888	Open Manhole	1200	F1.003	118.560	225	F1.002	118.560	225		
								F2.000	118.548	225		
F14	123.017	3.641	Open Manhole	1200	F3.000	119.376	225					
F15A	120.275	1.425	Open Manhole	1200	F4.000	118.850	225					
F15	120.107	2.310	Open Manhole	1200	F1.004	117.797	225	F1.003	117.797	225		
								F3.000	117.797	225		
								F4.000	117.797	225		
F16	119.577	1.983	Open Manhole	1200	F1.005	117.594	225	F1.004	117.594	225		
F17	119.402	1.883	Open Manhole	1200	F1.006	117.519	225	F1.005	117.519	225		
F18	121.630	1.619	Open Manhole	1200	F5.000	120.011	225					
F19	119.088	1.883	Open Manhole	1200	F1.007	117.205	225	F1.006	117.205	225		
								F5.000	117.663	225		458
F20	118.031	2.000	Open Manhole	1200	F1.008	116.031	225	F1.007	116.031	225		
F21	115.271	1.700	Open Manhole	1200	F1.009	113.571	225	F1.008	113.571	225		
F22	118.971	1.598	Open Manhole	1200	F6.000	117.373	225					

Atkins Limited		Page 7
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Manhole Schedules for Foul - Main

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam., L*W (mm)	PN	Pipe Out Invert Level (m)	Diameter (mm)	PN	Pipes In Invert Level (m)	Diameter (mm)	Backdrop (mm)
F23	117.698	1.778	Open Manhole	1200	F6.001	115.920	225	F6.000	116.233	225	313
F24	119.912	2.134	Open Manhole	1200	F7.000	117.778	225				
F25	118.015	1.425	Open Manhole	1200	F7.001	116.590	225	F7.000	116.590	225	
F26	117.135	1.738	Open Manhole	1200	F6.002	115.397	225	F6.001	115.397	225	
								F7.001	115.710	225	313
F27	116.755	1.738	Open Manhole	1200	F6.003	115.017	225	F6.002	115.017	225	
F28	118.056	1.425	Open Manhole	1200	F8.000	116.631	225				
F29	116.641	1.823	Open Manhole	1200	F6.004	114.818	225	F6.003	114.818	225	
								F8.000	115.131	225	313
F30	116.237	1.738	Open Manhole	1200	F6.005	114.499	225	F6.004	114.499	225	
F31	115.678	1.738	Open Manhole	1200	F6.006	113.940	225	F6.005	113.940	225	
F32	114.929	1.738	Open Manhole	1200	F6.007	113.191	225	F6.006	113.191	225	
F33	114.353	1.955	Open Manhole	1200	F1.010	112.398	225	F1.009	112.653	225	255
								F6.007	112.615	225	217
F34	113.050	1.650	Open Manhole	1200	F1.011	111.400	225	F1.010	111.400	225	
F35	109.957	1.425	Open Manhole	1200	F1.012	108.532	225	F1.011	108.532	225	
F36	107.980	1.425	Open Manhole	1200	F1.013	106.555	225	F1.012	106.555	225	
FEx CMH	107.530	1.192	Open Manhole	0		OUTFALL		F1.013	106.338	225	

Atkins Limited		Page 8
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Foul - Main

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F1.000	o	225	F5	123.190	120.985	1.980	Open Manhole	1200
F1.001	o	225	F6	122.332	120.486	1.621	Open Manhole	1200
F1.002	o	225	F8	121.828	118.775	2.828	Open Manhole	1200
F2.000	o	225	F12	120.950	119.325	1.400	Open Manhole	1200
F1.003	o	225	F13	121.436	118.560	2.651	Open Manhole	1200
F3.000	o	225	F14	123.017	119.376	3.416	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F1.000	29.947	60.0	F6	122.332	120.486	1.621	Open Manhole	1200
F1.001	17.355	60.1	F8	121.828	120.197	1.406	Open Manhole	1200
F1.002	12.882	59.9	F13	121.436	118.560	2.651	Open Manhole	1200
F2.000	34.519	44.4	F13	121.436	118.548	2.663	Open Manhole	1200
F1.003	61.036	80.0	F15	120.107	117.797	2.085	Open Manhole	1200
F3.000	53.673	34.0	F15	120.107	117.797	2.085	Open Manhole	1200

Atkins Limited		Page 9
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Foul - Main

Upstream Manhole

PN Sect	Hyd Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F4.000	o 225	F15A	120.275	118.850	1.200	Open Manhole	1200
F1.004	o 225	F15	120.107	117.797	2.085	Open Manhole	1200
F1.005	o 225	F16	119.577	117.594	1.758	Open Manhole	1200
F1.006	o 225	F17	119.402	117.519	1.658	Open Manhole	1200
F5.000	o 225	F18	121.630	120.011	1.394	Open Manhole	1200

Downstream Manhole

PN (m)	Length (1:X)	Slope	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F4.000	36.460	34.6	F15	120.107	117.797	2.085	Open Manhole	1200
F1.004	38.376	189.0	F16	119.577	117.594	1.758	Open Manhole	1200
F1.005	14.168	189.0	F17	119.402	117.519	1.658	Open Manhole	1200
F1.006	19.050	60.7	F19	119.088	117.205	1.658	Open Manhole	1200
F5.000	46.044	19.6	F19	119.088	117.663	1.200	Open Manhole	1200

Atkins Limited		Page 10
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Foul - Main

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F1.007	o	225	F19	119.088	117.205	1.658	Open Manhole	1200
F1.008	o	225	F20	118.031	116.031	1.775	Open Manhole	1200
F1.009	o	225	F21	115.271	113.571	1.475	Open Manhole	1200
F6.000	o	225	F22	118.971	117.373	1.373	Open Manhole	1200
F6.001	o	225	F23	117.698	115.920	1.553	Open Manhole	1200
F7.000	o	225	F24	119.912	117.778	1.909	Open Manhole	1200
F7.001	o	225	F25	118.015	116.590	1.200	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F1.007	25.575	21.8	F20	118.031	116.031	1.775	Open Manhole	1200
F1.008	38.723	15.7	F21	115.271	113.571	1.475	Open Manhole	1200
F1.009	21.189	23.1	F33	114.353	112.653	1.475	Open Manhole	1200
F6.000	50.261	44.1	F23	117.698	116.233	1.240	Open Manhole	1200
F6.001	22.860	43.7	F26	117.135	115.397	1.513	Open Manhole	1200
F7.000	29.693	25.0	F25	118.015	116.590	1.200	Open Manhole	1200
F7.001	21.057	23.9	F26	117.135	115.710	1.200	Open Manhole	1200

Atkins Limited		Page 11
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Foul - Main

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F6.002	o	225	F26	117.135	115.397	1.513	Open Manhole	1200
F6.003	o	225	F27	116.755	115.017	1.513	Open Manhole	1200
F8.000	o	225	F28	118.056	116.631	1.200	Open Manhole	1200
F6.004	o	225	F29	116.641	114.818	1.598	Open Manhole	1200
F6.005	o	225	F30	116.237	114.499	1.513	Open Manhole	1200
F6.006	o	225	F31	115.678	113.940	1.513	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F6.002	10.927	28.8	F27	116.755	115.017	1.513	Open Manhole	1200
F6.003	16.379	82.3	F29	116.641	114.818	1.598	Open Manhole	1200
F8.000	74.944	50.0	F29	116.641	115.131	1.285	Open Manhole	1200
F6.004	17.208	53.9	F30	116.237	114.499	1.513	Open Manhole	1200
F6.005	27.110	48.5	F31	115.678	113.940	1.513	Open Manhole	1200
F6.006	23.807	31.8	F32	114.929	113.191	1.513	Open Manhole	1200

Atkins Limited		Page 12
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:12 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Foul - Main

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F6.007	o	225	F32	114.929	113.191	1.513	Open Manhole	1200
F1.010	o	225	F33	114.353	112.398	1.730	Open Manhole	1200
F1.011	o	225	F34	113.050	111.400	1.425	Open Manhole	1200
F1.012	o	225	F35	109.957	108.532	1.200	Open Manhole	1200
F1.013	o	225	F36	107.980	106.555	1.200	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
F6.007	15.194	26.4	F33	114.353	112.615	1.513	Open Manhole	1200
F1.010	32.780	32.8	F34	113.050	111.400	1.425	Open Manhole	1200
F1.011	53.685	18.7	F35	109.957	108.532	1.200	Open Manhole	1200
F1.012	38.476	19.5	F36	107.980	106.555	1.200	Open Manhole	1200
F1.013	14.946	68.9	FEX CMH	107.530	106.338	0.967	Open Manhole	0

Atkins Limited		Page 1
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	
Date 02/03/2021 12:06 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Summary of Critical Results by Maximum Level (Rank 1) for Foul - Main

Simulation Criteria

Areal Reduction Factor 1.000 Manhole Headloss Coeff (Global) 0.500 MADD Factor * 10m³/ha Storage 4.000
 Hot Start (mins) 0 Foul Sewage per hectare (l/s) 0.000 Inlet Coeffiecient 0.800
 Hot Start Level (mm) 0 Additional Flow - % of Total Flow 0.000 Flow per Person per Day (l/per/day) 0.000

Number of Input Hydrographs 0 Number of Offline Controls 0 Number of Time/Area Diagrams 0
 Number of Online Controls 0 Number of Storage Structures 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR M5-60 (mm) 17.000 Cv (Summer) 0.750
 Region Scotland and Ireland Ratio R 0.238 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm) 300.0 DVD Status ON
 Analysis Timestep 2.5 Second Increment (Extended) Inertia Status ON
 DTS Status ON

Profile(s) Summer and Winter
 Duration(s) (mins) 15, 30, 60, 120, 180, 240, 360, 480, 600, 720, 960, 1440
 Return Period(s) (years) 2, 5, 30, 100
 Climate Change (%) 10, 10, 10, 10

US/MH PN	Name	Storm	Return Period	Climate Change	First (X) First (Y) First (Z)			Overflow Flood	Overflow	Water Level (m)	Surcharged Depth (m)	Flooded Volume (m ³)	Flow / Overflow Cap. (l/s)	Pipe Flow (l/s)	Status
					First (X)	First (Y)	First (Z)								
F1.000	F5	600 Winter	2	+10%						120.987	-0.223	0.000	0.00	0.1	OK
F1.001	F6	480 Winter	2	+10%						120.490	-0.221	0.000	0.00	0.2	OK

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	Page 2
Date 02/03/2021 12:06 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Summary of Critical Results by Maximum Level (Rank 1) for Foul - Main

US/MH Level

PN Name Exceeded

F1.000	F5
F1.001	F6

Atkins Limited										Page 3
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW			CNWQR Phase 4a Foul Design							
Date 02/03/2021 12:06 File Foul Network 2_4a Updated Feb2021.MDX			Designed by JK Checked by MK							
Innovyze			Network 2018.1							



Summary of Critical Results by Maximum Level (Rank 1) for Foul - Main

US/MH PN	Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Water			Surcharged		Flooded		Pipe	
									Level (m)	Depth (m)	Volume (m³)	Flow / Cap.	Overflow (l/s)	Flow (l/s)	Status		
F1.002	F8	120 Winter	5	+10%					118.779	-0.221	0.000	0.00		0.2	OK		
F2.000	F12	60 Winter	5	+10%					119.328	-0.222	0.000	0.00		0.2	OK		
F1.003	F13	360 Summer	100	+10%					118.575	-0.210	0.000	0.01		0.7	OK		
F3.000	F14	120 Winter	5	+10%					119.380	-0.221	0.000	0.00		0.3	OK		
F4.000	F15A	30 Winter	5	+10%					118.854	-0.221	0.000	0.00		0.3	OK		
F1.004	F15	600 Summer	30	+10%					117.828	-0.194	0.000	0.05		1.5	OK		
F1.005	F16	180 Winter	30	+10%					117.627	-0.192	0.000	0.05		1.5	OK		
F1.006	F17	180 Winter	5	+10%					117.545	-0.199	0.000	0.03		1.7	OK		
F5.000	F18	120 Winter	5	+10%					120.013	-0.223	0.000	0.00		0.2	OK		
F1.007	F19	1440 Summer	100	+10%					117.228	-0.202	0.000	0.02		2.1	OK		
F1.008	F20	60 Winter	5	+10%					116.054	-0.202	0.000	0.02		2.4	OK		
F1.009	F21	960 Summer	100	+10%					113.596	-0.200	0.000	0.03		2.6	OK		
F6.000	F22	15 Winter	5	+10%					117.379	-0.219	0.000	0.01		0.4	OK		
F6.001	F23	120 Winter	5	+10%					115.928	-0.217	0.000	0.01		0.5	OK		
F7.000	F24	120 Winter	5	+10%					117.780	-0.223	0.000	0.00		0.2	OK		
F7.001	F25	120 Winter	5	+10%					116.593	-0.222	0.000	0.00		0.3	OK		
F6.002	F26	120 Winter	5	+10%					115.410	-0.212	0.000	0.01		0.9	OK		
F6.003	F27	120 Winter	5	+10%					115.037	-0.205	0.000	0.02		0.9	OK		
F8.000	F28	720 Summer	100	+10%					116.637	-0.219	0.000	0.01		0.4	OK		
F6.004	F29	120 Winter	5	+10%					114.841	-0.202	0.000	0.02		1.3	OK		
F6.005	F30	120 Winter	5	+10%					114.522	-0.202	0.000	0.02		1.4	OK		
F6.006	F31	120 Winter	5	+10%					113.961	-0.204	0.000	0.02		1.5	OK		
F6.007	F32	720 Winter	2	+10%					113.211	-0.205	0.000	0.02		1.5	OK		
F1.010	F33	480 Summer	30	+10%					112.432	-0.191	0.000	0.05		4.1	OK		
F1.011	F34	480 Summer	30	+10%					111.429	-0.196	0.000	0.04		4.1	OK		

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	Page 4
Date 02/03/2021 12:06 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Summary of Critical Results by Maximum Level (Rank 1) for Foul - Main

PN	US/MH	Level
	Name	Exceeded

F1.002	F8
F2.000	F12
F1.003	F13
F3.000	F14
F4.000	F15A
F1.004	F15
F1.005	F16
F1.006	F17
F5.000	F18
F1.007	F19
F1.008	F20
F1.009	F21
F6.000	F22
F6.001	F23
F7.000	F24
F7.001	F25
F6.002	F26
F6.003	F27
F8.000	F28
F6.004	F29
F6.005	F30
F6.006	F31
F6.007	F32
F1.010	F33

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Foul Design	Page 5
Date 02/03/2021 12:06 File Foul Network 2_4a Updated Feb2021.MDX	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Summary of Critical Results by Maximum Level (Rank 1) for Foul - Main

US/MH	Level	
PN	Name	Exceeded
F1.011	F34	

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW		CNWQR Phase 4a Foul Design	Page 6
Date 02/03/2021 12:06 File Foul Network 2_4a Updated Feb2021.MDX		Designed by JK Checked by MK	
Innovyze			Network 2018.1

Summary of Critical Results by Maximum Level (Rank 1) for Foul - Main

PN	US/MH Name	Storm Period	Return Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Water	Surcharged	Flooded	Pipe			
								Level (m)	Depth (m)	Volume (m³)	Flow / Cap.	Overflow (l/s)	Flow (l/s)	Status
F1.012	F35	360 Summer	5	+10%				108.561	-0.196	0.000	0.04		4.1	OK
F1.013	F36	480 Summer	100	+10%				106.598	-0.182	0.000	0.08		4.1	OK

US/MH Level
PN Name Exceeded

F1.012 F35
F1.013 F36

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	Page 1
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for Storm Network

Pipe Sizes STANDARD Manhole Sizes STANDARD

FSR Rainfall Model - Scotland and Ireland

Return Period (years)	2	Foul Sewage (l/s/ha)	0.000	Maximum Backdrop Height (m)	1.600
M5-60 (mm)	17.000	Volumetric Runoff Coeff.	0.750	Min Design Depth for Optimisation (m)	1.200
Ratio R	0.238	PIMP (%)	100	Min Vel for Auto Design only (m/s)	1.00
Maximum Rainfall (mm/hr)	50	Add Flow / Climate Change (%)	0	Min Slope for Optimisation (1:X)	500
Maximum Time of Concentration (mins)	30	Minimum Backdrop Height (m)	0.650		

Designed with Level Soffits

Network Design Table for Storm Network

« - Indicates pipe capacity < flow

PN	Length	Fall	Slope	I.Area	T.E.	Base	k	HYD	DIA	Section	Type	Auto
(m)	(m)	(1:X)	(ha)	(mins)	(mins)	Flow	(l/s)	(mm)	SECT	(mm)		Design

Network Results Table

PN	Rain	T.C.	US/IL	Σ	I.Area	Σ	Base	Foul	Add	Flow	Vel	Cap	Flow
(mm/hr)	(mins)	(m)		(ha)		Flow	(l/s)	(l/s)	(l/s)	(m/s)	(l/s)	(l/s)	(l/s)

Atkins Limited		Page 2
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Network Design Table for Storm Network

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
S2.000	28.096	0.511	55.0	0.050	4.00	0.0	0.600	o	300	Pipe/Conduit	🔒
S2.001	17.367	0.316	55.0	0.036	0.00	0.0	0.600	o	300	Pipe/Conduit	🔒
S2.002	12.706	0.231	55.0	0.026	0.00	0.0	0.600	o	300	Pipe/Conduit	🔒
S3.000	35.841	0.211	169.9	0.075	4.00	0.0	0.600	o	375	Pipe/Conduit	🔒
S2.003	58.196	0.707	82.3	0.000	0.00	0.0	0.600	o	375	Pipe/Conduit	🔒
S4.000	50.706	1.525	33.2	0.203	4.00	0.0	0.600	o	225	Pipe/Conduit	🔒

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
S2.000	50.00	4.22	120.947	0.050	0.0	0.0	0.0	2.12	150.2	6.7
S2.001	49.69	4.36	120.436	0.086	0.0	0.0	0.0	2.13	150.2	11.6
S2.002	49.32	4.46	119.470	0.112	0.0	0.0	0.0	2.12	150.2	15.0
S3.000	49.42	4.43	119.375	0.075	0.0	0.0	0.0	1.39	153.2	10.0
S2.003	47.63	4.94	119.164	0.187	0.0	0.0	0.0	2.00	220.7	24.1
S4.000	49.63	4.37	120.132	0.203	0.0	0.0	0.0	2.28	90.5	27.3

Atkins Limited		Page 3
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Network Design Table for Storm Network

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
S5.000	36.505	0.243	150.2	0.131	4.00	0.0	0.600	o	225	Pipe/Conduit	
S2.004	40.509	0.455	89.0	0.202	0.00	0.0	0.600	o	450	Pipe/Conduit	
S2.005	14.168	0.175	81.0	0.062	0.00	0.0	0.600	o	450	Pipe/Conduit	
S2.006	17.588	0.389	45.2	0.047	0.00	0.0	0.600	o	450	Pipe/Conduit	
S6.000	44.490	1.542	28.9	0.123	4.00	0.0	0.600	o	225	Pipe/Conduit	
S2.007	29.295	0.382	76.7	0.059	0.00	0.0	0.600	o	450	Pipe/Conduit	
S2.008	38.230	0.760	50.3	0.224	0.00	0.0	0.600	o	450	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
S5.000	48.91	4.57	118.850	0.131	0.0	0.0	0.0	1.06	42.3	17.3
S2.004	46.62	5.25	118.382	0.723	0.0	0.0	0.0	2.16	342.8	91.3
S2.005	46.29	5.36	117.927	0.785	0.0	0.0	0.0	2.26	359.6	98.4
S2.006	46.00	5.46	117.752	0.832	0.0	0.0	0.0	3.03	481.9	103.6
S6.000	49.89	4.30	119.130	0.123	0.0	0.0	0.0	2.45	97.2	16.6
S2.007	45.37	5.67	116.763	1.014	0.0	0.0	0.0	2.32	369.5	124.6
S2.008	44.73	5.89	114.381	1.238	0.0	0.0	0.0	2.87	456.8	149.9

Atkins Limited		Page 4
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Network Design Table for Storm Network

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
S2.009	23.035	0.468	49.2	0.048	0.00	0.0	0.600	o	450	Pipe/Conduit	🔒
S7.000	49.948	1.015	49.2	0.158	4.00	0.0	0.600	o	225	Pipe/Conduit	🔓
S7.001	20.609	0.488	42.2	0.051	0.00	0.0	0.600	o	300	Pipe/Conduit	🔓
S8.000	29.946	1.050	28.5	0.119	4.00	0.0	0.600	o	225	Pipe/Conduit	🔓
S8.001	18.889	0.805	23.5	0.061	0.00	0.0	0.600	o	225	Pipe/Conduit	🔓
S7.002	13.041	0.380	34.3	0.018	0.00	0.0	0.600	o	300	Pipe/Conduit	🔓
S7.003	18.156	0.296	61.3	0.027	0.00	0.0	0.600	o	300	Pipe/Conduit	🔓

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
S2.009	44.36	6.02	113.021	1.286	0.0	0.0	0.0	2.90	461.8	154.5
S7.000	49.36	4.45	117.213	0.158	0.0	0.0	0.0	1.87	74.3	21.1
S7.001	48.85	4.59	116.198	0.209	0.0	0.0	0.0	2.43	171.5	27.7
S8.000	50.00	4.20	117.565	0.119	0.0	0.0	0.0	2.46	97.8	16.1
S8.001	49.83	4.32	116.515	0.180	0.0	0.0	0.0	2.71	107.9	24.4
S7.002	48.57	4.67	115.710	0.407	0.0	0.0	0.0	2.69	190.3	53.6
S7.003	48.05	4.82	115.330	0.434	0.0	0.0	0.0	2.01	142.2	56.4

Atkins Limited		Page 5
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Network Design Table for Storm Network

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
S9.000	76.088	1.522	50.0	0.212	4.00	0.0	0.600	o	225	Pipe/Conduit	o
S7.004	15.114	0.297	50.9	0.019	0.00	0.0	0.600	o	300	Pipe/Conduit	o
S7.005	27.110	0.559	48.5	0.105	0.00	0.0	0.600	o	375	Pipe/Conduit	o
S7.006	23.807	0.749	31.8	0.081	0.00	0.0	0.600	o	375	Pipe/Conduit	o
S7.007	15.771	0.326	48.4	0.021	0.00	0.0	0.600	o	450	Pipe/Conduit	o
S2.010	30.842	1.350	22.8	0.045	0.00	0.0	0.600	o	450	Pipe/Conduit	o
S2.011	54.345	2.896	18.8	0.068	0.00	0.0	0.600	o	450	Pipe/Conduit	o

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
S9.000	48.51	4.68	116.556	0.212	0.0	0.0	0.0	1.85	73.7	27.9
S7.004	47.66	4.93	115.034	0.665	0.0	0.0	0.0	2.21	156.2	85.8
S7.005	47.10	5.11	114.737	0.770	0.0	0.0	0.0	2.61	288.0	98.2
S7.006	46.70	5.23	114.178	0.851	0.0	0.0	0.0	3.22	356.1	107.6
S7.007	46.42	5.32	113.029	0.871	0.0	0.0	0.0	2.93	465.8	109.6
S2.010	44.03	6.14	112.553	2.202	0.0	0.0	0.0	4.27	678.8	262.6
S2.011	43.52	6.33	111.203	2.270	0.0	0.0	0.0	4.71	749.1	267.6

Atkins Limited		Page 6
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Network Design Table for Storm Network

PN	Length (m)	Fall (1:X)	Slope (ha)	I.Area (mins)	T.E. (ha)	Base Flow (1/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
S2.012	35.114	1.341	26.2	0.000	0.00	0.0	0.600	o	300	Pipe/Conduit	🔒
S2.013	15.617	0.306	51.0	0.000	0.00	0.0	0.600	o	300	Pipe/Conduit	🔒

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (1/s)	Foul Flow (1/s)	Add Flow (1/s)	Vel (m/s)	Cap (1/s)	Flow (1/s)
S2.012	43.03	6.52	108.057	2.270	0.0	0.0	0.0	3.08	218.1	267.6
S2.013	42.73	6.64	106.641	2.270	0.0	0.0	0.0	2.21	155.9	267.6



WoodCote Grove
Ashley Road, Epsom
Surrey, KT18 5BW
Date 26/02/2021 16:11
File Storm Network 2_4a Updated_Feb2021_No US ...

CNWQR
Phase 4a Storm Design

Designed by JK
Checked by MK

Innovyze

Network 2018.1

Manhole Schedules for Storm Network

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam., L*W (mm)	Pipe Out			PN	Pipes In			Backdrop (mm)
					PN	Invert Level (m)	Diameter (mm)		PN	Invert Level (m)	Diameter (mm)	
S5	123.190	2.243	Open Manhole	1200	S2.000	120.947	300					
S6	122.332	1.896	Open Manhole	1200	S2.001	120.436	300	S2.000	120.436	300		
S7	121.828	2.358	Open Manhole	1200	S2.002	119.470	300	S2.001	120.120	300		650
S12	120.950	1.575	Open Manhole	1350	S3.000	119.375	375					
S13	121.436	2.272	Open Manhole	1350	S2.003	119.164	375	S2.002	119.239	300		
								S3.000	119.164	375		
S14	123.018	2.886	Open Manhole	1200	S4.000	120.132	225					
S15A	120.275	1.425	Open Manhole	1200	S5.000	118.850	225					
S15	120.032	1.650	Open Manhole	1350	S2.004	118.382	450	S2.003	118.457	375		
								S4.000	118.607	225		
								S5.000	118.607	225		
S16	119.577	1.650	Open Manhole	1350	S2.005	117.927	450	S2.004	117.927	450		
S17	119.402	1.650	Open Manhole	1350	S2.006	117.752	450	S2.005	117.752	450		
S18	121.630	2.500	Open Manhole	1200	S6.000	119.130	225					
S19	119.088	2.325	Open Manhole	1350	S2.007	116.763	450	S2.006	117.363	450	600	
								S6.000	117.588	225	600	
S20	118.031	3.650	Open Manhole	1350	S2.008	114.381	450	S2.007	116.381	450	2000	
S21	115.271	2.250	Open Manhole	1350	S2.009	113.021	450	S2.008	113.621	450	600	
S22	118.971	1.758	Open Manhole	1200	S7.000	117.213	225					



WoodCote Grove
Ashley Road, Epsom
Surrey, KT18 5BW

CNWQR
Phase 4a Storm Design

Date 26/02/2021 16:11

Designed by JK

File Storm Network 2_4a Updated_Feb2021_No US ...

Checked by MK

Innovyze

Network 2018.1

Manhole Schedules for Storm Network

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam., L*W (mm)	Pipe Out			PN	Pipes In			Backdrop (mm)
					PN	Invert Level (m)	Diameter (mm)		PN	Invert Level (m)	Diameter (mm)	
S23	117.698	1.500	Open Manhole	1200	S7.001	116.198	300	S7.000	116.198	225		
S24	119.912	2.347	Open Manhole	1200	S8.000	117.565	225					
S25	118.015	1.500	Open Manhole	1050	S8.001	116.515	225	S8.000	116.515	225		
S26	117.135	1.425	Open Manhole	1050	S7.002	115.710	300	S7.001	115.710	300		
								S8.001	115.710	225		
S27	116.755	1.425	Open Manhole	1050	S7.003	115.330	300	S7.002	115.330	300		
S28	118.056	1.500	Open Manhole	1050	S9.000	116.556	225					
S29	116.641	1.607	Open Manhole	1050	S7.004	115.034	300	S7.003	115.034	300		
								S9.000	115.034	225		
S30	116.237	1.500	Open Manhole	1050	S7.005	114.737	375	S7.004	114.737	300		
S31	115.678	1.500	Open Manhole	1050	S7.006	114.178	375	S7.005	114.178	375		
S32	114.929	1.900	Open Manhole	1050	S7.007	113.029	450	S7.006	113.429	375	325	
S33	114.353	1.800	Open Manhole	1500	S2.010	112.553	450	S2.009	112.553	450		
								S7.007	112.703	450	150	
S34	113.050	1.847	Open Manhole	1500	S2.011	111.203	450	S2.010	111.203	450		
S35	109.957	1.900	Open Manhole	1500	S2.012	108.057	300	S2.011	108.307	450	400	
S36	107.980	1.339	Open Manhole	1500	S2.013	106.641	300	S2.012	106.716	300	75	
SO/F 1	106.935	0.600	Open Manhole	1200		OUTFALL		S2.013	106.335	300		

Atkins Limited		Page 9
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Storm Network

Upstream Manhole

PN	Hyd	Diam	MH	C.Level	I.Level	D.Depth	MH	MH DIAM., L*W
	Sect	(mm)	Name	(m)	(m)	(m)	Connection	(mm)
S2.000	o	300	S5	123.190	120.947	1.943	Open Manhole	1200
S2.001	o	300	S6	122.332	120.436	1.596	Open Manhole	1200
S2.002	o	300	S7	121.828	119.470	2.058	Open Manhole	1200
S3.000	o	375	S12	120.950	119.375	1.200	Open Manhole	1350
S2.003	o	375	S13	121.436	119.164	1.897	Open Manhole	1350
S4.000	o	225	S14	123.018	120.132	2.661	Open Manhole	1200

Downstream Manhole

PN	Length	Slope	MH	C.Level	I.Level	D.Depth	MH	MH DIAM., L*W
	(m)	(1:X)	Name	(m)	(m)	(m)	Connection	(mm)
S2.000	28.096	55.0	S6	122.332	120.436	1.596	Open Manhole	1200
S2.001	17.367	55.0	S7	121.828	120.120	1.408	Open Manhole	1200
S2.002	12.706	55.0	S13	121.436	119.239	1.897	Open Manhole	1350
S3.000	35.841	169.9	S13	121.436	119.164	1.897	Open Manhole	1350
S2.003	58.196	82.3	S15	120.032	118.457	1.200	Open Manhole	1350
S4.000	50.706	33.2	S15	120.032	118.607	1.200	Open Manhole	1350

Atkins Limited		Page 10
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Storm Network

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
S5.000	o	225	S15A	120.275	118.850	1.200	Open Manhole	1200
S2.004	o	450	S15	120.032	118.382	1.200	Open Manhole	1350
S2.005	o	450	S16	119.577	117.927	1.200	Open Manhole	1350
S2.006	o	450	S17	119.402	117.752	1.200	Open Manhole	1350
S6.000	o	225	S18	121.630	119.130	2.275	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
S5.000	36.505	150.2	S15	120.032	118.607	1.200	Open Manhole	1350
S2.004	40.509	89.0	S16	119.577	117.927	1.200	Open Manhole	1350
S2.005	14.168	81.0	S17	119.402	117.752	1.200	Open Manhole	1350
S2.006	17.588	45.2	S19	119.088	117.363	1.275	Open Manhole	1350
S6.000	44.490	28.9	S19	119.088	117.588	1.275	Open Manhole	1350

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	Page 11
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

PIPELINE SCHEDULES for Storm Network

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
S2.007	o	450	S19	119.088	116.763	1.875	Open Manhole	1350
S2.008	o	450	S20	118.031	114.381	3.200	Open Manhole	1350
S2.009	o	450	S21	115.271	113.021	1.800	Open Manhole	1350
S7.000	o	225	S22	118.971	117.213	1.533	Open Manhole	1200
S7.001	o	300	S23	117.698	116.198	1.200	Open Manhole	1200
S8.000	o	225	S24	119.912	117.565	2.122	Open Manhole	1200
S8.001	o	225	S25	118.015	116.515	1.275	Open Manhole	1050

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
S2.007	29.295	76.7	S20	118.031	116.381	1.200	Open Manhole	1350
S2.008	38.230	50.3	S21	115.271	113.621	1.200	Open Manhole	1350
S2.009	23.035	49.2	S33	114.353	112.553	1.350	Open Manhole	1500
S7.000	49.948	49.2	S23	117.698	116.198	1.275	Open Manhole	1200
S7.001	20.609	42.2	S26	117.135	115.710	1.125	Open Manhole	1050
S8.000	29.946	28.5	S25	118.015	116.515	1.275	Open Manhole	1050
S8.001	18.889	23.5	S26	117.135	115.710	1.200	Open Manhole	1050

Atkins Limited		Page 12
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Storm Network

Upstream Manhole

PN	Hyd	Diam	MH	C.Level	I.Level	D.Depth	MH	MH DIAM., L*W
	Sect	(mm)	Name	(m)	(m)	(m)	Connection	(mm)
S7.002	o	300	S26	117.135	115.710	1.125	Open Manhole	1050
S7.003	o	300	S27	116.755	115.330	1.125	Open Manhole	1050
S9.000	o	225	S28	118.056	116.556	1.275	Open Manhole	1050
S7.004	o	300	S29	116.641	115.034	1.307	Open Manhole	1050
S7.005	o	375	S30	116.237	114.737	1.125	Open Manhole	1050
S7.006	o	375	S31	115.678	114.178	1.125	Open Manhole	1050

Downstream Manhole

PN	Length	Slope	MH	C.Level	I.Level	D.Depth	MH	MH DIAM., L*W
	(m)	(1:X)	Name	(m)	(m)	(m)	Connection	(mm)
S7.002	13.041	34.3	S27	116.755	115.330	1.125	Open Manhole	1050
S7.003	18.156	61.3	S29	116.641	115.034	1.307	Open Manhole	1050
S9.000	76.088	50.0	S29	116.641	115.034	1.382	Open Manhole	1050
S7.004	15.114	50.9	S30	116.237	114.737	1.200	Open Manhole	1050
S7.005	27.110	48.5	S31	115.678	114.178	1.125	Open Manhole	1050
S7.006	23.807	31.8	S32	114.929	113.429	1.125	Open Manhole	1050

Atkins Limited		Page 13
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



PIPELINE SCHEDULES for Storm Network

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
S7.007	o	450	S32	114.929	113.029	1.450	Open Manhole	1050
S2.010	o	450	S33	114.353	112.553	1.350	Open Manhole	1500
S2.011	o	450	S34	113.050	111.203	1.397	Open Manhole	1500
S2.012	o	300	S35	109.957	108.057	1.600	Open Manhole	1500
S2.013	o	300	S36	107.980	106.641	1.039	Open Manhole	1500

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
S7.007	15.771	48.4	S33	114.353	112.703	1.200	Open Manhole	1500
S2.010	30.842	22.8	S34	113.050	111.203	1.397	Open Manhole	1500
S2.011	54.345	18.8	S35	109.957	108.307	1.200	Open Manhole	1500
S2.012	35.114	26.2	S36	107.980	106.716	0.964	Open Manhole	1500
S2.013	15.617	51.0	SO/F 1	106.935	106.335	0.300	Open Manhole	1200

Atkins Limited		Page 14
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Free Flowing Outfall Details for Storm Network

Outfall Pipe Number	Outfall C. Name	I. Level (m)	Min I. Level (m)	D, L (mm)	W (m)
---------------------	-----------------	--------------	------------------	-----------	-------

S2.013	SO/F 1	106.935	106.335	0.000	1200	0
--------	--------	---------	---------	-------	------	---

Simulation Criteria for Storm Network

Volumetric Runoff Coeff	0.750	Manhole Headloss Coeff (Global)	0.500	Inlet Coeffiecient	0.800
Areal Reduction Factor	1.000	Foul Sewage per hectare (l/s)	0.000	Flow per Person per Day (l/per/day)	0.000
Hot Start (mins)	0	Additional Flow - % of Total Flow	0.000	Run Time (mins)	60
Hot Start Level (mm)	0	MADD Factor * 10m³/ha Storage	4.000	Output Interval (mins)	1

Number of Input Hydrographs	0	Number of Offline Controls	0	Number of Time/Area Diagrams	0
Number of Online Controls	2	Number of Storage Structures	1	Number of Real Time Controls	0

Synthetic Rainfall Details

Rainfall Model	FSR	M5-60 (mm)	17.000	Cv (Summer)	0.750
Return Period (years)	2	Ratio R	0.238	Cv (Winter)	0.840
Region	Scotland and Ireland	Profile Type	Summer Storm Duration (mins)		15

Atkins Limited		Page 15
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Online Controls for Storm Network

Hydro-Brake® Optimum Manhole: S13, DS/PN: S2.003, Volume (m³): 7.9

Unit Reference	MD-CHE-0226-3500-1800-3500	Sump Available	No		
Design Head (m)	1.800	Diameter (mm)	226		
Design Flow (l/s)	35.0	Invert Level (m)	119.164		
Flush-Flo™	Calculated	Minimum Outlet Pipe Diameter (mm)	300		
Objective	Minimise upstream storage	Suggested Manhole Diameter (mm)	1500		
Application	Surface				
Control Points	Head (m)	Flow (l/s)	Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.800	35.0	Kick-Flo®	0.629	21.3
Flush-Flo™	0.460	34.9	Mean Flow over Head Range	-	26.1

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)								
0.100	6.2	0.600	21.5	1.600	33.0	2.600	41.9	5.000	57.8
0.200	18.4	0.800	23.5	1.800	35.0	3.000	45.0	5.500	60.5
0.300	27.0	1.000	26.2	2.000	36.8	3.500	48.5	6.000	63.2
0.400	33.4	1.200	28.7	2.200	38.6	4.000	51.8	6.500	65.7
0.500	33.1	1.400	30.9	2.400	40.3	4.500	54.9	7.000	68.2

Atkins Limited		Page 16
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Hydro-Brake® Manhole: S34, DS/PN: S2.011, Volume (m³): 7.9

Design Head (m) 1.000 Design Flow (l/s) 260.0 Hydro-Brake® Type Md10 Diameter (mm) 434 Invert Level (m) 111.203

Depth (m)	Flow (l/s)										
0.100	16.1	0.600	161.1	1.600	332.4	2.600	423.7	5.000	587.6	7.500	719.6
0.200	41.3	0.800	215.7	1.800	352.5	3.000	455.1	5.500	616.2	8.000	743.2
0.300	70.1	1.000	259.1	2.000	371.6	3.500	491.6	6.000	643.6	8.500	766.1
0.400	100.5	1.200	287.8	2.200	389.7	4.000	525.5	6.500	669.9	9.000	788.3
0.500	131.2	1.400	310.9	2.400	407.1	4.500	557.4	7.000	695.2	9.500	809.9

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	Page 17
Date 26/02/2021 16:11 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Storage Structures for Storm Network

Tank or Pond Manhole: S34, DS/PN: S2.011

Invert Level (m) 111.203

Depth (m)	Area (m ²)										
0.000	315.0	0.200	315.0	0.400	315.0	0.600	315.0	0.800	315.0	1.000	315.0
0.100	315.0	0.300	315.0	0.500	315.0	0.700	315.0	0.900	315.0	1.100	0.0

Atkins Limited		Page 1
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:13 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Summary of Critical Results by Maximum Level (Rank 1) for Storm Network

Simulation Criteria

Areal Reduction Factor 1.000 Manhole Headloss Coeff (Global) 0.500 MADD Factor * 10m³/ha Storage 4.000
 Hot Start (mins) 0 Foul Sewage per hectare (l/s) 0.000 Inlet Coeffiecient 0.800
 Hot Start Level (mm) 0 Additional Flow - % of Total Flow 0.000 Flow per Person per Day (l/per/day) 0.000

Number of Input Hydrographs 0 Number of Offline Controls 0 Number of Time/Area Diagrams 0
 Number of Online Controls 2 Number of Storage Structures 1 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR M5-60 (mm) 17.000 Cv (Summer) 0.750
 Region Scotland and Ireland Ratio R 0.238 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm) 300.0 DVD Status ON
 Analysis Timestep 2.5 Second Increment (Extended) Inertia Status ON
 DTS Status ON

Profile(s) Summer and Winter
 Duration(s) (mins) 15, 30, 60, 120, 180, 240, 360, 480, 600, 720, 960, 1440
 Return Period(s) (years) 2, 5, 30, 100
 Climate Change (%) 10, 10, 10, 10

US/MH PN	Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Water Level	Surcharged Depth	Flooded Volume (m ³)	Flow / Overflow Cap. (l/s)	Pipe Flow (l/s)	Status
									(m)	(m)	(m ³)	(l/s)	(l/s)	
S2.000	S5	15 Winter	100	+10%					121.023	-0.224	0.000	0.15	18.6	OK
S2.001	S6	30 Winter	100	+10%					120.547	-0.189	0.000	0.20	26.1	OK

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	Page 2
Date 26/02/2021 16:13 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	

Summary of Critical Results by Maximum Level (Rank 1) for Storm Network

US/MH	Level	
PN	Name	Exceeded
S2.000	S5	
S2.001	S6	

Atkins Limited										Page 3
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW				CNWQR Phase 4a Storm Design						
Date 26/02/2021 16:13 File Storm Network 2_4a Updated_Feb2021_No US ...				Designed by JK Checked by MK						
Innovyze Network 2018.1										



Summary of Critical Results by Maximum Level (Rank 1) for Storm Network

PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Water Level	Surcharged Depth	Flooded Volume	Flow / Cap.	Pipe Flow (l/s)
									(m)	(m)	(m ³)	(l/s)	(l/s)
S2.002	S7	30 Winter	100	+10%	30/15 Summer				120.531	0.761	0.000	0.24	29.5
S3.000	S12	30 Winter	100	+10%	30/15 Summer				120.526	0.776	0.000	0.12	16.1
S2.003	S13	30 Winter	100	+10%	30/15 Summer				120.516	0.977	0.000	0.16	30.4
S4.000	S14	15 Winter	100	+10%					120.295	-0.062	0.000	0.88	76.0
S5.000	S15A	15 Winter	100	+10%	100/15 Summer				119.157	0.082	0.000	1.14	45.7
S2.004	S15	15 Winter	100	+10%					118.693	-0.139	0.000	0.80	214.8
S2.005	S16	15 Winter	100	+10%					118.299	-0.078	0.000	1.00	235.7
S2.006	S17	15 Winter	100	+10%					118.036	-0.166	0.000	0.71	251.3
S6.000	S18	15 Winter	100	+10%					119.242	-0.113	0.000	0.50	46.1
S2.007	S19	15 Winter	100	+10%					117.147	-0.066	0.000	0.99	314.5
S2.008	S20	15 Winter	100	+10%					114.739	-0.092	0.000	0.96	389.4
S2.009	S21	15 Winter	100	+10%	100/15 Summer				113.872	0.401	0.000	1.03	393.5
S7.000	S22	15 Winter	100	+10%					117.370	-0.068	0.000	0.82	58.7
S7.001	S23	15 Winter	100	+10%	100/15 Summer				116.616	0.118	0.000	0.47	70.0
S8.000	S24	15 Winter	100	+10%					117.676	-0.114	0.000	0.49	44.6
S8.001	S25	15 Winter	100	+10%					116.707	-0.033	0.000	0.67	65.3
S7.002	S26	15 Winter	100	+10%	30/15 Summer				116.418	0.408	0.000	0.83	127.7
S7.003	S27	15 Winter	100	+10%	30/15 Summer				116.148	0.518	0.000	1.11	136.3
S9.000	S28	15 Winter	100	+10%	100/15 Summer				117.010	0.229	0.000	0.89	64.1
S7.004	S29	15 Winter	100	+10%	30/15 Summer				115.769	0.435	0.000	1.57	206.2
S7.005	S30	15 Winter	100	+10%					115.027	-0.085	0.000	0.94	237.2
S7.006	S31	15 Winter	100	+10%					114.448	-0.105	0.000	0.86	262.5
S7.007	S32	15 Winter	100	+10%	100/15 Summer				113.628	0.149	0.000	0.81	262.2
S2.010	S33	15 Winter	100	+10%	100/15 Summer				113.406	0.403	0.000	1.11	651.8
S2.011	S34	60 Winter	100	+10%	5/30 Summer				112.185	0.532	0.000	0.37	255.7

Atkins Limited		Page 4
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:13 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Summary of Critical Results by Maximum Level (Rank 1) for Storm Network

PN	US/MH Name	Level	
		Status	Exceeded
S2.002	S7 SURCHARGED		
S3.000	S12 SURCHARGED		
S2.003	S13 SURCHARGED		
S4.000	S14 OK		
S5.000	S15A SURCHARGED		
S2.004	S15 OK		
S2.005	S16 OK		
S2.006	S17 OK		
S6.000	S18 OK		
S2.007	S19 OK		
S2.008	S20 OK		
S2.009	S21 SURCHARGED		
S7.000	S22 OK		
S7.001	S23 SURCHARGED		
S8.000	S24 OK		
S8.001	S25 OK		
S7.002	S26 SURCHARGED		
S7.003	S27 SURCHARGED		
S9.000	S28 SURCHARGED		
S7.004	S29 SURCHARGED		
S7.005	S30 OK		
S7.006	S31 OK		
S7.007	S32 SURCHARGED		
S2.010	S33 SURCHARGED		

Atkins Limited WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	Page 5
Date 26/02/2021 16:13 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Summary of Critical Results by Maximum Level (Rank 1) for Storm Network

PN	US/MH	Level	
	Name	Status	Exceeded
S2.011	S34	SURCHARGED	

Atkins Limited		Page 6
WoodCote Grove Ashley Road, Epsom Surrey, KT18 5BW	CNWQR Phase 4a Storm Design	
Date 26/02/2021 16:13 File Storm Network 2_4a Updated_Feb2021_No US ...	Designed by JK Checked by MK	
Innovyze	Network 2018.1	



Summary of Critical Results by Maximum Level (Rank 1) for Storm Network

PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Water Level	Surcharged Depth	Flooded Volume	Flow / Overflow Cap.	Pipe Flow (l/s)
									(m)	(m)	(m ³)	(l/s)	(l/s)
S2.012	S35	60 Winter	100	+10%	30/30	Winter			109.906	1.549	0.000	1.26	253.7
S2.013	S36	60 Winter	100	+10%	5/30	Winter			107.761	0.820	0.000	1.93	253.7

PN	US/MH Name	Level	
		Status	Exceeded
S2.012	S35	FLOOD RISK	
S2.013	S36	FLOOD RISK	



Member of the SNC-Lavalin Group

Cork NW Regeneration Quarter - Phase 4A

Stage 1 Road Safety Audit

Cork City Council

April2021

Notice

This document and its contents have been prepared and are intended solely for Cork City Council's information and use in relation to the Cork North West Regeneration Quarter Phase 4A.

Atkins assumes no responsibility to any other party in respect of or arising out of or in connection with this document and/or its contents.

Document history

Client signoff

Client	Cork City Council
Project	Cork North West Regeneration Quarter – Phase 4A
Job number	5204404

Contents

Chapter	Page
1. Introduction	4
1.1. Background	4
1.2. Site Inspection	4
1.3. The Team	4
1.4. The Design	4
1.5. Road Safety Audit Compliance	5
1.6. Road Safety Audit Compliance	5
2. Road Safety Issues Identified	7
2.1. Problem: Parking spaces within the turning area	7
2.2. Problem: Misaligned tactile paving	7
2.3. Problem: Use of link road as a Rat-Run	8
2.4. Problem: Pedestrian Crossing located away from the Desire Line	8
2.5. Problem: Shared Space Detailing	9
2.6. Problem: Potential Adverse Camber	9
2.7. Problem: Vehicle Speed on Knocknaheeny Avenue	10
3. Audit Team Statement	11
3.1. Certification	11
3.2. Sole Purpose	11
3.3. Implementation of RSA Recommendations	11
3.4. Audit Team's Independence to the Design Process	11
3.5. Road Safety Audit Team Sign-Off	11
4. Designers Response	12
4.1. Preparing a Response to the Road Safety Audit	12
4.2. Returning the Feedback Form	12
4.3. Triggering the Need for an Exception Report	12
Appendix A. Audit Team Approvals	14
A.1. Team Leader	15
A.2. Team Member	16
Appendix B. Road Safety Audit Feedback Form	17

Tables

Table 1-1 - Drawing List	4
Table 1-2 - Summary of Collision Characteristics	6

1. Introduction

1.1. Background

This report describes the findings of a Stage 1 Road Safety Audit associated with the Cork North West Regeneration Quarter – Phase 4A.

The scheme involves the construction of new residential units on an infill site between Knocknaheeny Ave. and Killala Green in Cork City. The site audited at this time is that site designated as Phase 4A under the City Northwest Quarter Regeneration Masterplan, Knocknaheeny.

The Stage 1 Audit has been completed in April 2021 by Atkins on behalf of Cork City Council.

1.2. Site Inspection

The site visit was undertaken on the 8th of April 2021. In accordance with current Government Level 5 Covid-19 restrictions the site visit has been undertaken with all necessary precautions in place i.e. team members travel in separate vehicles, social distancing observed on site and all post visit discussions were completed by telephone.

1.3. The Team

The Road Safety Audit Team members were as follows:

- Team Leader: **Keith Barry** BE (Hons) CEng MIEI
- Team Member: **James Bohan** MEng Nat Dip Eng CEng MIEI

A copy of the TII approval documentation for the audit team is included in Appendix A.

1.4. The Design

The following drawings were examined as part of the Road Safety Audit (RSA) process:

Table 1-1 - Drawing List

Drawing No	Drawing Title	Revision
CNW-P4A-ATK-P4A-Z0-DR-C-950100	Proposed Road Layout and Indicative Road Levels	P01
CNW-P4A-ATK-P4A-Z0-DR-C-950120	Proposed Road Layout Long section	P01
CNW-P4A-ATK-P4A-Z0-DR-C-950131	Proposed Road Layout Junction Sight Lines Sheet 2	P01
CNW-P4A-ATK-P4A-Z0-DR-C-950700	Proposed Pavement Layout Plan	P01
CNW-P4A-ATK-P4A-Z0-DR-C-950705	Proposed Route Types	A
CNW-P4A-ATK-P4A-Z0-DR-C-950750	Proposed Road Layout Plan Vehicle Tracking Analysis	P01
CNW-P4A-ATK-P4A-Z0-DR-C-951200	Proposed Road Signs and Traffic Markings	P01
RK5137848/C/435	Proposed Public Lighting Layout	B

1.5. Road Safety Audit Compliance

Procedure and Scope

This Road Safety Audit has been carried out in accordance with the procedures and scope set out in TII publication number **GE-STY-01024 - Road Safety Audit**.

As part of the road safety audit process, the Audit Team have examined only those issues within the design which relate directly to road safety.

Compliance with Design Standards

The road safety audit process is not a design check, therefore verification or compliance with design standards has not formed part of the audit process.

Minimising Risk of Collision Occurrence

All problems described in this report are considered by the Audit Team to require action in order to improve the safety of the scheme and minimise the risk of collision occurrence.

1.6. Road Safety Audit Compliance

No existing collision statistical information was provided, and a review of the Road Safety Authority online collision database indicates that there were no recorded collisions within the scheme area between 2005 and 2016 inclusive. There are 4 no. collisions recorded on the adjacent Knocknaheeny Ave. One involved a pedestrian which resulted in minor injuries and the other three were vehicle incidents at the junction of Knocknaheeny Road and Harbour View Road. It should be noted that the RSA collision database is not a comprehensive record and does not include damage only collisions or any collisions recorded since 2016.

The location of these four collisions has been indicated in Figure 1-1, with the collision characteristics summarised in Table 1-2. Of the four recorded collisions one (25%) involved pedestrians or cyclists. As the scheme will introduce additional residential properties to the area it is likely that VRU numbers will increase, thus the design proposals should ensure that priority and protection is given to VRUs in the urban environment, and that overall vehicle speeds are reduced.




Figure 1-1 - RSA Collision Database 2005 - 2016

No.	Severity	Casualties	Year	Vehicle	Circumstances	Day	Time
1	Minor	1	2011	Car	Pedestrian	Tues	16.00-19.00
2	Minor	1	2007	Car	Other	Sun	16.00-19.00
3	Minor	2	2008	Car	Other	Wed	10.00-16.00
4	Minor	4	2012	Car	Rear end, straight	Mon	19.00-23.00

Table 1-2 - Summary of Collision Characteristics


2. Road Safety Issues Identified

2.1. Problem: Parking spaces within the turning area

Location: Northern end of side road 07

The proposed turning area at the end of side road 07 (cul-de-sac) contains parking bays. Vehicles using these spaces will have to either reverse out of the turning area, putting vulnerable road users at risk or will have to attempt at three-point turn manoeuvre within the turning area increasing the risk of material damage collisions.

Figure 2-1 – Parking within turning area



Recommendation

It is recommended that the designer should provide additional paved area at the end of the turning area to facilitate manoeuvres of exiting vehicles.

2.2. Problem: Misaligned tactile paving

Location: Northern end of side road 07

The tactile paving at the proposed pedestrian crossing at the northern end of side road 07 appears to be misaligned. Tactile paving should align with the tactile paving on the opposite side of the road to ensure visually impaired users are correctly guided across the road. Misaligned paving could result in visually impaired users walking out into the carriageway in front of oncoming vehicles.

Figure 2-2 – Misaligned tactile paving



Recommendation


The tactile paving, throughout the scheme should be checked to ensure it properly aligns with the opposite side of the road crossing.

2.3. Problem: Use of link road as a Rat-Run

Location: Junction of Link road and Killala Green

There is the potential for the new link road through Phase 4A to be used as a Rat-Run with the associated risk of increased speeds. This could put pedestrians along the road but particularly at the junction with Killala Green at risk of collision with vehicles, leading to pedestrian/vehicle type collisions which may result in serious injury.

Figure 2-3 – Use of Link road as a Rat-Run



Recommendation


In keeping with the treatments at other junctions on the scheme consideration should be given to the use of a ramp at the entrance / pedestrian crossing at this location.

2.4. Problem: Pedestrian Crossing located away from the Desire Line

Location: Junction of Side Road 10 and Link road

The pedestrian crossing at this location does not appear to align with the likely pedestrian desire line. This could result in pedestrians crossing away from the designated location, which could catch a driver unaware resulting in a risk of a vehicle / pedestrian collision.

Figure 2-4 – Pedestrian Crossing located away from the Desire Line



Recommendation

It is recommended that the designer should consider relocation of the crossing closer to the pedestrian desire line.

2.5. Problem: Shared Space Detailing

Location: Southern end of the north – South spine road

The detail for the shared space at the above location (Drawing CNW-P4A-ATK-P4A-Z0-DR-C-950700) does not indicate any footpaths immediately in front of the houses. This has the potential to bring vehicles and pedestrians into conflict.

Figure 2-5 – Shared Space Detailing



Recommendation

It is recommended that the designer should consider a buffer zone between the housing and the vehicle accessible shared space to give pedestrians comfort when entering / exiting the houses.

2.6. Problem: Potential Adverse Camber

Location: Junction of Side Road 10 and Link Road

With the downhill gradient on the Link Road creates the potential for the introduction of adverse camber at the junction with Side Road 10. Adverse camber can lead to several difficulties including drainage issues, uncomfortable ride quality for drivers and difficulty in manoeuvring large vehicle such as refuse trucks.

Figure 2-6 – Potential Adverse Camber



Recommendation


It is recommended that the designer should consider the geometry of the link road / side road tie-in to ensure a free draining smooth interface is provided.

2.7. Problem: Vehicle Speed on Knocknaheeny Avenue

Location: Knocknaheeny Avenue

During the site visit several vehicles were observed travelling at a higher than appropriate speed on Knocknaheeny Avenue in the direction of Harbour View Road. The scheme proposes to introduce uncontrolled crossings at two locations on Knocknaheeny Avenue. Pedestrians crossing at these locations are potentially at risk of collision.

Figure 2-7 – Vehicle Speed on Knocknaheeny Avenue



Recommendation

It is recommended that the designer should consider providing some advance warning measures in association with the introduction of the pedestrian crossings, which increase driver awareness of the pedestrians at the crossings and thus encouraging them to travel at an appropriate speed on approach. These measures could include additional advance warning signage, modified road markings and ensuring adequate public lighting is provided at these locations.

3. Audit Team Statement

3.1. Certification

We certify that we have examined the drawings and documents listed in Chapter 1 of this Report.

3.2. Sole Purpose

The Road Safety Audit has been carried out with the sole purpose of identifying any features of the design which could be removed or modified in order to improve the road safety aspects of the scheme.

3.3. Implementation of RSA Recommendations

The problems identified herein have been noted in the Report together with their associated recommendations for road safety improvements. We (the Audit Team) propose that these recommendations should be studied with a view to implementation.

3.4. Audit Team's Independence to the Design Process

No member of the Audit Team has been otherwise involved with the design of the measures audited.

3.5. Road Safety Audit Team Sign-Off

Keith Barry

Audit Team Leader

Road Safety Engineering Team

ATKINS

Signed:



Date: 12th April 2021

James Bohan

Audit Team Member

Road Safety Engineering Team

ATKINS

Signed:



Date: 12th April 2021

4. Designers Response

4.1. Preparing a Response to the Road Safety Audit

The Designer should prepare an Audit Response for each of the recommendations using the Road Safety Audit Feedback Form attached in Appendix A.

When completed, this form should be signed by the Designer and returned to the Audit Team.

4.2. Returning the Feedback Form

Please return the completed Road Safety Audit Feedback Form attached in Appendix A of this report to the following email or postal address:

Email address: Keith.Barry@atkinsglobal.com

Postal address: WS Atkins
Unit 2B
2200 Cork Airport Business Park
Cork
T12 R279

Telephone: 00 353 (0)21 429 0300

The Audit Team will consider the Designers response and reply indicating acceptance or otherwise of the Designers response to each recommendation.

4.3. Triggering the Need for an Exception Report

If the situation arises where the Designer and the Audit Team cannot agree on an appropriate means of addressing an underlying safety issue identified as part of the audit process, an Exception Report must be prepared by the Designer on each disputed item listed in the audit report.

Appendices

Appendix A. Audit Team Approvals

A.1. Team Leader

*Keith Barry
Atkins House
150 Lakeside Drive
Airside Business Park
Swords, Co.Dublin*

Date: 20/12/2019

Ref: KB217558

re: APPROVAL AS ROAD SAFETY AUDITOR

Dear Keith Barry,

You meet the qualification and experience requirements for Road Safety Audit as follows:

Scheme Category	Audit Team Status	Team Leader Expiry Date
Road Scheme	Team Leader	31/12/2021
Development Scheme	Team Leader	31/12/2021

The above assessment is based on information supplied and the qualification and experience requirements of National Roads Authority in accordance with HD 19 "Road Safety Audit". Further approval through RSAAS must be sought for the proposed road safety audit team for each audit undertaken on a National Road.

Yours sincerely,

Lucy Curtis

*Regional Road Safety Engineer
roadsafetyaudits@ti.ie*

A.2. Team Member

James Bohan
Atkins House
150 Lakeside Drive
Airside Business Park
Swords, Co. Dublin

Date: 13/06/2016

Ref: JB*182

re: APPROVAL AS ROAD SAFETY AUDITOR

Dear James Bohan,

You meet the qualification and experience requirements for Road Safety Audit as follows:

Scheme Category	Audit Team Status	Team Leader Expiry Date
Road Scheme	Team Member	
Development Scheme	Team Member	

The above assessment is based on information supplied and the qualification and experience requirements of National Roads Authority in accordance with HD 19 "Road Safety Audit". Further approval through RSAAS must be sought for the proposed road safety audit team for each audit undertaken on a National Road.

Yours sincerely,

Lucy Curtis

Regional Road Safety Engineer
roadsafetyaudits@tti.ie

Appendix B. Road Safety Audit Feedback Form

Scheme: Cork NW Regeneration Quarter - Phase 4A

Audit Stage: Stage 1 Road Safety Audit

Date Audit Completed: 12th April 2021

		To be completed by the Designer		To be completed by the Audit Team
Paragraph No. in Safety Audit Report	Problem accepted (yes/no)	Recommended measure accepted (yes/no)	Alternative measures or comments	Alternative Measures accepted by Auditors (yes/no)
2.1	Yes	Yes		
2.2	Yes	Yes		
2.3	Yes	Yes		
2.4	Yes	Yes		
2.5	Yes	Yes	Boundary wall to be introduced in front of the units so no safety concerns regarding individuals stepping from front door onto shared surface.	
2.6	Yes	Yes	To be addressed at detailed design	
2.7	Yes	Yes	Crossing points to be positioned at existing public lighting pole locations to ensure appropriate lighting levels and advanced warning signs to be installed.	

Signed by the Designer: Martin O Sullivan

Date: 18.04.2021

Martin O Sullivan

Signed by the Audit Team Leader:

Date: 19 / 04 / 2021

Keith Barry

Signed by the Employer:

Date: 19.04.2021

Marian Hutchinson

WS Atkins International Limited

Atkins House
150 Airside Business Park
Swords
Co. Dublin
K67 K5W4

Tel: +353 1 810 8000

DATE: 14 April 2021
DESIGNER: NS
PROJECT No: 5204404 Rev A
PROJECT NAME: Housing Development Knocknaheeny Avenue, Cork - Atkins



Residential area designed in accordance with EN13201-2:2015
Category P3.

Outdoor Lighting Report

Coastal Quater - Bray

PREPARED BY: Design Software from:
Atkins Limited,
150 Airside Business Park,
Swords,
Co. Dublin, Ireland

Layout Report

General Data

Dimensions in Metres Angles in Degrees

Grid Origin 565610.2m x 572901.3m

Area 260.4m x 217.3m

Sample Spacing 1.50m x 1.50m

Luminaires



Luminaire A Data


Supplier	C U Phosco
Type	P852-24-S1-NW-W7-0350-26W
Lamp(s)	740SS NW
Lamp Flux (klm)	3.55
File Name	P852-24-S1-NW-W7-0350-26W.ies
Maintenance Factor	0.89
Imax70,80,90(cd/klm)	502.8, 86.6, 0.0
No. in Project	15

Layout

ID	Type	X	Y	Height	Angle	Tilt	Cant	Out-reach	Target X	Target Y	Target Z
1	A	565712.72	572971.18	6.00	309.00	0.00	0.00	0.40			
2	A	565734.31	572975.87	6.00	135.00	0.00	0.00	0.40			
3	A	565726.85	572986.81	6.00	43.00	0.00	0.00	0.40			
4	A	565723.44	573008.40	6.00	229.00	0.00	0.00	0.40			
5	A	565699.96	573020.32	6.00	40.00	0.00	0.00	0.40			
6	A	565742.54	572969.59	6.00	38.00	0.00	0.00	0.40			
7	A	565685.56	573035.86	6.00	317.00	0.00	0.00	0.40			
8	A	565759.83	572961.87	6.00	229.00	0.00	0.00	0.40			
9	A	565751.23	573002.64	6.00	314.00	0.00	0.00	0.40			
10	A	565773.71	573012.60	6.00	142.00	0.00	0.00	0.40			
11	A	565771.96	573037.59	6.00	351.00	0.00	0.00	0.40			
12	A	565781.18	573062.81	6.00	197.00	0.00	0.00	0.40			
13	A	565793.57	573024.87	6.00	135.00	0.00	0.00	0.40			
14	A	565808.55	573037.18	6.00	132.00	0.00	0.00	0.40			
15	A	565798.08	573050.40	6.00	358.00	0.00	0.00	0.40			


Polar Diagram

Luminaire A P852-24-S1-NW-W7-0350-26W



Horizontal Illuminance (lux)

Grid 1



Results

Eav	8.50
Emin	1.60
Emax	18.87
Emin/Emax	0.08
Emin/Eav	0.19

Horizontal Illuminance (lux)

Grid 1




Results

Eav	8.50
Emin	1.60
Emax	18.87
Emin/Emax	0.08
Emin/Eav	0.19

Horizontal Illuminance (lux)

Grid 1



Results

Eav	8.50
Emin	1.60
Emax	18.87
Emin/Emax	0.08
Emin/Eav	0.19

City North Quarter Regeneration Phase 4A

**Engineering & Energy Report (Part L
Requirement)
Housing Agency Ltd**

31 March 2021

Contains *sensitive* information



Notice

This document and its contents have been prepared and are intended solely for Housing Agency information and use in relation for Planning Purposes.

WS Atkins International Limited assumes no responsibility to any other party in respect of or arising out of or in connection with this document and/or its contents.

This document has 11 pages including the cover.

Document history

Job number: 5204404			Document ref: R01			
Revision	Purpose description	Originated	Checked	Reviewed	Authorised	Date
Rev 01	Part 8 Planning	NS/MT	AK	NS	MOS	31/03/21

Client signoff

Client	Housing Agency
Project	City North Quarter Regeneration – Phase 4A
Document title	Engineering & Energy Report (Part L Requirement)
Job no.	5204404
Document No.	5204404/ATK/MEP/DG0001
Document Reference	R01

Table of contents

Chapter	Pages
Outline	4
1. Part L of the Building Regulation Design	5
1.1. Public Lighting Standards	5
1.2. Health & Safety	6
1.3. Public Lighting Design Requirement:	6
1.4. Lighting Classes Proposed	7
1.5. Trees & Arboriculture	7
2. Energy Statement/ Nearly Zero Energy Building (NZEB)	8
2.1. Energy Statement	9
2.2. E-Car Charging Provision	9
2.3. Design Information:	9

Outline

This document has been prepared and checked in accordance with Atkins BS OHSAS 18001:2007, EN ISO 9001:2015 and EN ISO 14001:2015.

This document has been prepared by Atkins, with all practical experience, caution and persistent work within the terms of the Contract with the Client, take into account of the resources devoted to us by agreement with the Client.

Atkins reject any responsibility to the Client and others in respect of any matters outside the scope of the above.

This document is confidential to the Client and Atkins accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at its own risk.

1. Part L of the Building Regulation Design

1.1. Public Lighting Standards

This section outlines the proposed public lighting schemes for the proposed residential development on lands at Knocknaheany Avenue and Killala Gardens, Co. Cork, Phase 4A.

The Energy efficiency requirements for lighting design will be compliance with Building Services Guides. Minimum efficacy standards for light fittings will be defined as a very high light specification quality, energy efficiency and future proofed external and internal lighting for City North Quarter Regeneration site development for Cork City Council (CCC) and Housing Agency.

The site development public lighting will be designed to its CCC specific requirements, illuminance level and uniformity to meet the lighting class for each area. All works will comply with the latest editions of the relevant standards, in particular the works shall be designed to take full account of:

- BS EN 13201 part 2 – Road Lighting Performance requirements.
- BS EN 13201 Part 3 – Road Lighting Details calculation of performance.
- BS EN 13201 Part 4 – Details methods of measuring light performance.
- The Current British Standards for Road Lighting are BS 5489 and BS EN 13201.
- BS EN 60529 - Specification for Degrees of Protection for enclosures.
- BS EN 60598-2-3 - Luminaires for Road and Street Lighting.
- BS 5489 -1 - Code of Practice for the design of road lighting.
- BS EN ISO 1461 Hot dip galvanized coatings on fabricated iron and steel articles. Specifications and test methods.
- IS EN 40-1 – Lighting Columns (Definitions and terms).
- IS EN 40-2- Lighting Columns (General requirements and dimensions).
- IS EN 40-3 - Lighting Columns (Design and verification and Verification by testing).
- IS EN 40-5 - Lighting Columns (Requirements for steel lighting columns).
- Roads Act, 1993. Road Traffic Act, 1994.
- Safety, Health and Welfare at Work Act 2005.
- Safety, Health and Welfare at Work Construction Regulations 2013.
- Building Control Act 2007.
- Road Traffic (Control of Traffic) Regulations 2006.
- ET 101 - National Rules for Electrical Installations published by ETCI.
- ET 211 - Code of Practice for Public Lighting Installations in Residential Areas published by ETCI.
- BS 7671 - Requirements for Electrical Installations. 7

Where a design standard has been revised, the latest edition will apply to all new lighting design / and installation.

1.2. Health & Safety

The attention of the Designer / Developer will be drawn to the obligations arising under the Safety, Health and Welfare at Work Act 2005 or latest approved version such as:

- Safety, Health and Welfare at Work (General Application) Regulations 2007 to 2012 or latest approved version.
- Safety, Health and Welfare at Work (Construction) regulations 2013 or latest approved version. Account will be taken of any traffic management measures that may be required during the installation of public lighting schemes including compliance with Chapter 8 of the Traffic Signals Manual published by the Department of Transport and CCC Public Lighting Department Requirement.

1.3. Public Lighting Design Requirement:

The site development public lighting installations will be designed by a competent public lighting engineer who has successfully completed the Institution of Lighting Professionals (ILP) Diploma in Exterior Lighting and is an active member of the Institution of Lighting Professionals, and as accepted by the CCC Public Lighting Department, to ensure that best practice is applied in the external lighting design of this residential development. This will include the requirement that public lighting schemes consider from junctions and traffic (both Pedestrian and Vehicular) conflict areas back i.e. T-junctions, pedestrian crossings, public and private car parking, etc.

All new systems of public lighting of a new development will be designed and installed in accordance with the requirements and as accepted by the CCC Public Lighting Department.

The overall lighting requirements for a specific area will be identified within the EN13201:2015, British and European design code. This will then be expanded and refined to take account of an area's unique character and needs in terms of vehicular/ pedestrian activity, location of local amenities, etc by the design brief. However, generally the requirements of the specific design code as stated above in Public Lighting Standards will be met.

As a general rule, new luminaires will be of LED technology source although consideration to alternative light sources (particularly for the purposes of floodlighting) will be given where appropriate. Whether there may be situations in popular locations used heavily at night a higher level of illumination will be anticipated. For particularly sensitive vicinity locations it will be recommended to arrange for trial installations to demonstrate the effectiveness of the lighting and its impact on surrounding areas. All luminaires will be manufactured to a minimum of IP 66 to BS EN 60590 for the lamp containment area and should be manufactured from vandal-resistant material. Lanterns will be designed and tested to provide a minimum normal operating life of 25 years.

Construction of lighting columns and luminaire specifications shall comply with the CCC Public Lighting Installations in Residential Guideline Document.

Lighting control and installation details shall also comply with the above document.

In determining levels of illumination, lighting positions and styles, the design brief will consider pedestrian and vehicular uses/needs in relation to the following:

- Areas of activity - Bus stops, paths, etc and areas of conflict (junctions, etc).
- Building heights.
- Street features - crossing points, sitting areas, tree planting, pinch-points, materials / colours, etc.
- Ground form levels (important to people with disabilities), hazards, etc.
- Local knowledge, incidence of vandalism, accident black spots, etc.

1.3.1. Obtrusive Lighting

Considerations will be given to the restriction of obtrusive light by:

- The control of the type of light source Restricting the level of light emitted by the luminaire at high angles usually between 70 and 90 degrees.
- The use of full horizontal cut off luminaires for mounting heights above 6m will have a substantial effect on restricting obtrusive light. Similarly, the use of shallow bowl luminaires for mounting heights of 6m or less will help to reduce the overall level of obtrusive light produced by road lighting installations, but may add to the numbers of lighting units required
- Careful consideration will be given to the design, installation, and maintenance of any lighting systems adjacent to the site to reduce the risk of damaging the night sight of the transport operators or reducing the visibility of signalling equipment.

1.4. Lighting Classes Proposed

The lighting classes assigned to the various locations within the development are outlined below and detailed in the public lighting report provided.

1.4.1. The Residential Areas

Residential areas will be designed using an 'P4' illuminance class derived from BS EN 13201. General street lighting will be installed on 6m columns.

1.4.2. Car Parks

Car parks are to be lit in accordance with BS5489-1:2013, recommendation as outlined in the CIBSE Lighting Guide and 'Secure by Design' guidance. The maintained illuminance level for the Car Park is proposed 20 lux. Car park luminaires will be installed on 8m columns.

Group switching of car park lighting will be facilitated via an astro-timer and photocell and a suitably rated contactor located within a dedicated feeder pillar.

1.4.3. Pedestrian Crossings

Pedestrian crossings will be lit in accordance with BS5489-1:2013 and ILP Technical Report 12.

The maintained illuminance level for the pedestrian crossing is proposed as follows:

- Average vertical illuminance on this axis of pedestrian crossing at a height of 1m: $Ev \geq 40$ lux
- Uniformity of vertical illuminance on lane in front of the driver (Ev_{min}/Ev_{av}): 0.20
- Average horizontal illuminance on pedestrian crossing at ground level: $Eh \geq 80$ lux
- Uniformity of horizontal illuminance (Eh_{min}/Eh_{av}): 0.30

Traffic route lighting and lighting of residential estates will be powered by landlord boards.

1.4.4. Cycleways

Cycleways will be lit in accordance with BS5489-1:2013 and BSEN 13201-2. Lighting columns positioned on cycleways will be set back a minimum of 0.5m to avoid contact with handlebars. Where the cycleway cannot be accessed by an elevated platform, raising and lowering columns will be installed. Raising and lowering columns shall be orientated so that the lantern head can be lowered safely without obstruction and, when in its collapsed position, shall not cause an obstruction to road users and pedestrians.

1.5. Trees & Arboriculture

Trees and other vegetation will not impede the functions of public lighting units. A separation of 5 metres between the lighting column and the outside of the crown will be allowed for the lighting to work as designed. Trees or vegetation will not be planted within 7 metres of a public light column.

The design will take into consideration the layout of the proposed public lighting column locations and the proposed landscape design. Both layouts will be coordinated to achieve the 7 metres separation between all trees and public lighting columns.

2. Energy Statement/ Nearly Zero Energy Building (NZEB)

The NZEB standard will apply to all buildings owned and occupied as refer to Department of Housing, Planning and Local Government and as per the building regulations and DEAP methodology. This will be equivalent to a 25% improvement in energy performance on the 2011 Building Regulations.

The key to Part L for NZEB compliance will include a Maximum Energy Performance Coefficient of 0.3, a Maximum Carbon Performance of 0.35 and a renewable Energy Ratio of 20%.

The cost optimal level is a primary energy performance of less than 125 kWh/m²/yr, when calculated using DEAP or upgrade of roof insulation and heating system. The nearly zero or very low amount of energy required will be covered to a very significant extent by energy from renewable sources, including energy from renewable sources produced on-site or nearby.

Proposed minimum threshold level compliance achieved with TGD L Dwellings as indicated below Fig 1: -




Figure 1 - Minimum Threshold Level Compliance

The design for the dwellings and apartments will include:

- LED lighting accounted for in DEAP (A+ bulbs, 94 lumen/cW, 4 W/m²)
- Efficient hot water uses in showers/taps accounted for in DEAP (125 l/p/d and 6l/min flow restrictor)
- Individual heat pumps for space heating and hot water production
- Mechanical ventilation for houses and apartments

2.1. Energy Statement

The proposed design strategy will ensure sustainable energy efficiency to ensure low running cost of use and consideration of green energy.

Some of considerations are listed below: -

- The apartment and houses to be designed will have a compact and efficient form, use of terrace and semidetached building formations limiting the heat loss and, where appropriate, availing of the heat gains through the fabric of the building
- Highly insulated external building façade
- Ensuring that the building is appropriately designed to limit overheating and hence the need for cooling
- Materials with long time life expectancy and low embodied energy.
- Consideration of water saving measures including water saving devices and controls and limiting the heat loss from pipes, ducts and vessels used for the transport or storage of heated water or air.
- Providing energy efficient space heating equipment, domestic hot water production systems, and ventilation systems, with effective controls.
- Providing energy efficient artificial lighting systems (LED) and adequate control of public and internal lighting systems.
- The guidance of the MEP design in compliance with Building Regulations Part L recommendations for conservation of fuel and energy setting of minimum energy performance requirements for building to achieve the Nearly Zero Energy Building, providing that the energy performance of the building is such as to limit the calculated primary energy consumption and related Carbon Dioxide (CO2) emissions as is reasonably practicable.
- Limitation of Carbon Dioxide (CO2) emissions to a Nearly Zero Energy Building level insofar as is reasonably practicable of for Landlord areas/ domestic buildings using the Energy Assessment Procedure (NEAP) published by Sustainable Energy Authority of Ireland.
- Ensuring that when a building element that forms part of the building envelope and has a significant impact on the energy performance of the building envelope, and the energy performance of the building element meets minimum energy performance requirements, functionally and economically feasible.
- The energy performance of each house/ and apartment will comply with the requirement of Part L building regulations and achieving no lower than a BER of A2.
- System design that provides to the building owner or occupants sufficient information about the building, the fixed building services, controls and their maintenance requirements so that the building can be operated in such a manner as to use no more fuel and energy than is reasonable.

2.2. E-Car Charging Provision

If required Electric Car (E-Car) charging points will be provided in accordance with CCC Development Plan 2016-2022.

2.3. Design Information:

The total estimated power electrical load for the phase 4A development have been based on BSRIA / Rules of Thumb Guidelines for building services (5th Edition) - CIBSE / Energy Benchmarks.

- A figure of 84(W/m²) is allowed for landlord areas. The figure is expressed in W/m² NIA, based on a net to gross ratio of 80% and mechanical power for plantrooms requirements (Rules of thumbs 5th edition / Energy Benchmarks).
- Predicting Electrical Future Load Growth - 10% power load growth factor is considered regarding future power expansion for the building associated with Building expansion and function of the building or facilities and Equipment technology within the building.
- Renewable Energy - Based on the Heat pumps systems.

- Rule of Thumb - Flats / Apartments 80(w/m²) electrical load. Note, Flat or apartment 7.5kw is employed with all electrical cooking and heating via heat pumps.
- Every house which has a parking space on curtilage to allow for a possible charging point. 20% of visitor spaces to allow for a possible charging point. Within the apartment Blocks, 20% of spaces to allow for a possible charging point with capacity to bring this up to 50%.
- The target efficiency for the apartment Blocks is 75% gross to net.
- Houses and Apartments Blocks heating and domestic hot water production will be achieved with individual heat pumps.
- Apartments can be assumed as 60sqm for 1-bed, 85 sqm for 2-beds and 110 sqm for 3 beds.
- Allowance to be made for EV charging points for future proofing and based on a minimum charging power per active charging station.

2.3.1. Metering Strategy

- Single Occupancy Dwellings & Apartments - The meters supplying the units will be located outside the building

Nari Shaqiri

Atkins
Atkins House
150-155 Airside Business Park
Swords
Co. Dublin

nari.shaqiri@atkinsglobal.com

Contains sensitive information
© Atkins Ltd except where stated otherwise.

The Atkins logo, 'Carbon Critical Design' and the strapline
'Plan Design Enable' are trademarks of Atkins Ltd.

Martin O' Sullivan

Unit 2B, 2200 Avenue 2000
Cork Airport Business Park
Co. Cork
T12R279

Uisce Éireann
Bosca OP 448
Oifig Sheachadta na
Cathrach Theas
Cathair Chorcaí

8 February 2021

Irish Water
PO Box 448,
South City
Delivery Office,
Cork City.

www.water.ie

Re: CDS21000293 pre-connection enquiry - Subject to contract | Contract denied

**Connection for Housing Development of 43 unit(s) at Cork North West Quarter Regeneration,
Kilmore Road Lower, Cork, Cork**

Dear Sir/Madam,

Irish Water has reviewed your pre-connection enquiry in relation to a Water & Wastewater connection at Cork North West Quarter Regeneration, Kilmore Road Lower, Cork, Cork (the **Premises**). Based upon the details you have provided with your pre-connection enquiry and on our desk top analysis of the capacity currently available in the Irish Water network(s) as assessed by Irish Water, we wish to advise you that your proposed connection to the Irish Water network(s) can be facilitated at this moment in time.

SERVICE	OUTCOME OF PRE-CONNECTION ENQUIRY
	<u>THIS IS NOT A CONNECTION OFFER. YOU MUST APPLY FOR A CONNECTION(S) TO THE IRISH WATER NETWORK(S) IF YOU WISH TO PROCEED.</u>
Water Connection	Feasible without infrastructure upgrade by Irish Water
Wastewater Connection	Feasible without infrastructure upgrade by Irish Water
SITE SPECIFIC COMMENTS	
Water Connection	Connections can be made to the water mains as per the drawings provided with this enquiry
Wastewater Connection	Connection can be made to the sewer at the south west of the site
The design and construction of the Water & Wastewater pipes and related infrastructure to be installed in this development shall comply with the Irish Water Connections and Developer Services Standard Details and Codes of Practice that are available on the Irish Water website. Irish Water reserves the right to supplement these requirements with Codes of Practice and these will be issued with the connection agreement.	

The map included below outlines the current Irish Water infrastructure adjacent to your site:



Reproduced from the Ordnance Survey of Ireland by Permission of the Government. License No. 3-3-34

Whilst every care has been taken in its compilation Irish Water gives this information as to the position of its underground network as a general guide only on the strict understanding that it is based on the best available information provided by each Local Authority in Ireland to Irish Water. Irish Water can assume no responsibility for and give no guarantees, undertakings or warranties concerning the accuracy, completeness or up to date nature of the information provided and does not accept any liability whatsoever arising from any errors or omissions. This information should not be relied upon in the event of excavations or any other works being carried out in the vicinity of the Irish Water underground network. The onus is on the parties carrying out excavations or any other works to ensure the exact location of the Irish Water underground network is identified prior to excavations or any other works being carried out. Service connection pipes are not generally shown but their presence should be anticipated.


General Notes:

- 1) The initial assessment referred to above is carried out taking into account water demand and wastewater discharge volumes and infrastructure details on the date of the assessment. **The availability of capacity may change at any date after this assessment.**
- 2) This feedback does not constitute a contract in whole or in part to provide a connection to any Irish Water infrastructure. All feasibility assessments are subject to the constraints of the Irish Water Capital Investment Plan.
- 3) The feedback provided is subject to a Connection Agreement/contract being signed at a later date.

- 4) A Connection Agreement will be required to commencing the connection works associated with the enquiry this can be applied for at <https://www.water.ie/connections/get-connected/>
- 5) A Connection Agreement cannot be issued until all statutory approvals are successfully in place.
- 6) Irish Water Connection Policy/ Charges can be found at <https://www.water.ie/connections/information/connection-charges/>
- 7) Please note the Confirmation of Feasibility does not extend to your fire flow requirements.
- 8) Irish Water is not responsible for the management or disposal of storm water or ground waters. You are advised to contact the relevant Local Authority to discuss the management or disposal of proposed storm water or ground water discharges
- 9) To access Irish Water Maps email datarequests@water.ie
- 10) All works to the Irish Water infrastructure, including works in the Public Space, shall have to be carried out by Irish Water.

If you have any further questions, please contact Brian O'Mahony from the design team on 022 52205 or email bomahony@water.ie For further information, visit www.water.ie/connections.

Yours sincerely,



Yvonne Harris

Head of Customer Operations



Member of the SNC-Lavalin Group

CORK NORTHWEST REGENERATION QUARTER; PHASE 4A

Engineering Planning Report

The Housing Agency

March 2022

Notice

This document and its contents have been prepared and are intended solely as information for The Housing Agency and use in relation to the development of a proposed Phase 4A site of the Cork Northwest Regeneration Quarter.

Atkins Ireland assumes no responsibility to any other party in respect of or arising out of or in connection with this document and/or its contents.

This document has 17 pages including the cover.

Document history

Client signoff

Client	The Housing Agency
Project	Cork Northwest Regeneration Quarter; Phase 4A
Job number	5204404
Client signature / date	

Contents

Chapter	Page
1. Introduction	4
2. Existing Site	5
2.1. Existing Site	5
2.2. Existing Civils	5
3. Roads & Traffic Engineering	6
3.1. Site Access and Circulation	6
3.2. Pavements	6
4. Potable Water Supply	7
4.1. Proposed Water Infrastructure	7
5. Foul Water Drainage	7
5.1. Proposed Foul Infrastructure	7
6. Surface Water Drainage	8
6.1. Proposed Surface Water Drainage	8
6.2. Site Design Details	8
Appendices	9
Appendix A. Foul Drainage Design Criteria and Manhole Schedules	10
Appendix B. Surface Water Drainage: Design Criteria, Pipeline Schedules, Flow Control Design and Network Simulation Results	11
Appendix C. Engineering Drawings	12
Appendix D. Stage 01; Road Safety Audit.	13
Appendix E. Public Lighting Report	14
Appendix F. Part L Report	15
Appendix G. Irish Water Pre-Connection Enquiry for Potable Water and Wastewater	16

1. Introduction

This Engineering Planning Report is submitted as part of the Part 8 planning application for Phase 4A of the Cork Northwest Regeneration Quarter. This report encompasses the Civil, Mechanical and Electrical aspects of the project. The Proposed Development site is the site of a former sports pitch on the northeast side of Knocknaheeny Avenue, on the north side of Cork City, County Cork.



Figure 01 Site Location.

The report and its appendixes address the following engineering aspects associated with the development;

- Road Engineering
- Foul Water Drainage
- Storm Drainage
- Potable Water Supply
- Part L Report
- Public Lighting

This report is to be read in conjunction with the applicable reports attached to this report and the Engineering Drawing set, as attached in Appendix C;

2. Existing Site

2.1. Existing Site

The existing site is the site of a former sports pitch on the northeast side of Knocknaheeny Avenue, on the north side of Cork City, County Cork.

The proposed site is considered brownfield and may have significant amounts of fill associated with the original housing developments in the areas dating back to the 1950's. The majority of the site is in pasture with an area to the southwest corner containing some elements of hardstanding. The proposal is to develop a 43-unit development on the site.

2.2. Existing Civils

The site slopes from North to South with a large embankment on the northern face increasing in height from West to East. The Southwest corner has been utilised as a storage depo by Cork City Council in the past and there are remnants of utilities in the area associated with the depo. A topographical survey of the existing site along with (GPR)/Utility surveys have been carried out.

The surveys have identified the following utilities/services in the vicinity of the site;

- Foul Water Drainage
- Storm Water Drainage
- Watermains
- Telecoms (Eircom and Virgin Media)
- Overhead & Underground Electrical Cables
- Gas
- ENet
- Public Lighting

3. Roads & Traffic Engineering

3.1. Site Access and Circulation

The roads infrastructure for the proposed development is as per the adopted Masterplan design for the regeneration project. Access to the site will be via Knocknaheeny Avenue at the southwest corner and Killala Gardens to the Northeast corner.

A Stage 01 Road Safety Audit has been completed for the proposed development and all actions called for in the audit have been accepted and addressed in the scheme design. Please refer to Appendix D for the Stage 01 RSA. Following consultation with Cork City Council Roads Department, it has been agreed to include for pedestrian crossing points across Knocknaheeny Avenue to facilitate mobility. These crossing points will consist of dropdown kerbs and tactile paving. Please refer to Appendix C & D for further details.

The road layout, road section widths and road build up have all been maintained in line with the adopted Masterplan design requirements. All shared surfaces will be maintained in line with the areas called up in the masterplan design.

The proposals outlined above has been discussed with Cork City Council with no objections raised to the proposed scheme.

3.2. Pavements

There are various pavement options proposed within the site comprising bituminous and concrete.

Trafficked areas:

Road - 200mm total bituminous on 150mm CL 804 on minimum capping required in line with TII MCDRW.

Car Parking Bays - 200mm total bituminous on 150mm CL 804 on minimum capping required in line with TII MCDRW.

Concrete Footpaths at vehicle cross over points – 225mm concrete on 150mm CL 804 on minimum capping required in line with TII MCDRW

Pedestrian areas:

Footpaths 100mm concrete on 150mm CL 804

4. Potable Water Supply

4.1. Proposed Water Infrastructure

The potable water supply for the proposed development has been designed in accordance with Irish Water Code of Practice and Standard Construction Details.

It is proposed to provide the watermains infrastructure across the phase in line with the masterplan design, which will encompass 150mm diameter, 100mm diameter and 63mm diameter lines. The water main infrastructure will take into account tie in locations for future phases in line with the masterplan design. The phase will be connected to the water infrastructure of Phase 3B which is to the Southwest of the site. Refer to Appendix C for watermain layout drawings.

An Irish Water Pre-Connection Enquiry has been submitted to Irish Water for the proposed water demand based on the information contained within this Planning Report and the adopted masterplan design. A letter of confirmation of feasibility (reference no. CDS21000293) has been received from Irish Water for the proposal as outlined above. Refer to Appendix G for a copy of confirmation of feasibility letter.

5. Foul Water Drainage

5.1. Proposed Foul Infrastructure

It is proposed to provide a foul water pipe network in line with the adopted masterplan design for Phase 4A. There has been an allowance made for the future tie in of phases in line with the masterplan. Phase 4A will tie directly into the new foul infrastructure constructed as part of Phase 3B which is situated to the southwest of the site.

An Irish Water Pre-Connection Enquiry has been submitted to Irish Water for the proposed foul layout based on the information contained within this Planning Report and the adopted masterplan design. A letter of confirmation of feasibility (reference no. CDS21000293) has been received from Irish Water for the proposal as outlined above. Refer to Appendix G for a copy of conformation of feasibility letter.

“MicroDrainage” which is an industry standard tool for design and assessment of gravity sewer drainage networks has been used to model the proposed foul network. The MicroDrainage model shows that the proposed foul network has adequate capacity for the flows that will be generated from the proposed development and will achieve self-cleansing velocities. The foul network has been designed to achieve self-cleansing velocity in the pipe system at least once per day. This varies for pipe sizes with full bore self-cleansing are in accordance with Irish Water Wastewater Code of Practice.

Refer to Appendix A for design criteria and manhole schedules for the foul drainage network and to Appendix C for Proposed Foul Water Drainage Layouts.

The entire foul water network will be constructed in accordance with Irish Water Code of Practice and Standard Details.

6. Surface Water Drainage

6.1. Proposed Surface Water Drainage

It is proposed that the development site will collect the surface water runoff and discharge the flow under gravity conditions into the storm infrastructure network as adopted under the masterplan design. Pipe diameters will vary from 225mm to 450mm allowing all tie in location invert levels to future phases to be maintained as per the masterplan design.

“MicroDrainage” which is an industry standard tool for design and assessment of gravity sewer drainage networks has been used to model the proposed surface water network. The MicroDrainage model shows that the proposed surface water network has adequate capacity for the flows that will be generated from the proposed development and will achieve the full bore self-cleansing velocities

A hydro-brake manhole has been included on the line to allow for future installation of a flow control device, once the attenuation is constructed which is part of Phase 5A of the masterplan. The flow control device will be designed and installed as part of Phase 5A storm water design strategy.

Given the nature of site, the surface water runoff overland flow has been considered and site levels designed accordingly. Proposed levels allow surface water runoff to fall away and avoid ponding around buildings by grading pavements towards either the eastern, western or southern landscaping areas ensuring the critical infrastructure will be protected during exceedance events.

Surface Water Drainage will be constructed with the Greater Dublin Code of Practice for Drainage Works Version 6.0 and Cork City Council standards and details.

Refer to Appendix B for surface water drainage schedules and simulation results along with Appendix C for Proposed Surface Water Drainage Layouts.

6.2. Site Design Details

A minimum cover of 1.2m has been provided for the proposed network to give sufficient cover to soffit level within road locations, with a minimum slope specified to achieve self-cleansing velocities to reduce drainage depths at the downstream of the site. Steeper gradients have been proposed in the northern section of drainage by the access road to maintain the minimum 1.2m cover. Where the desired 1.2m cover cannot be achieved, an absolute minimum 900mm is proposed and surround the pipe in concrete to ensure adequate protection is maintained.

The proposed impermeable areas have been incorporated into the hydraulic model, with 100% of impermeable areas applied to the drainage network. The Phase 4A roads shall drain via traditional proprietary products such as kerb, gullies and drains to the storm water network.

The proposed surface water design was designed to provide the following.

- No surcharging in the 1 in 5-year storm event.
- No flooding in the 1 in 30-year storm event.
- No flooding against a 1 in 100-year storm event (including climate change allowance) or controlled flooding allowing the volume to be contained on site and not impact the surrounding infrastructure.

Appendices



Appendix A. Foul Drainage Design Criteria and Manhole Schedules

Appendix B. Surface Water Drainage: Design Criteria, Pipeline Schedules, Flow Control Design and Network Simulation Results

Appendix C. Engineering Drawings

Appendix D. Stage 01; Road Safety Audit.

Appendix E. Public Lighting Report

Appendix F. Part L Report

Appendix G. Irish Water Pre-Connection Enquiry for Potable Water and Wastewater

WS Atkins Ireland Ltd,
Atkins House
150 Airside Business Park
Swords
Co. Dublin
K67 K5W4

© WS Atkins Ireland Ltd except where stated otherwise